


Mini Level Revo



76416



76418



76417




76423



76387



76347



76065



76064

*Gradient cannot be measured with vial graduations.
●Parts are listed from p.274

Item Code	Description	Body Size (mm)	Weight (g)	JAN Code	Packing Unit	Packaging
76416	Lineclip Model	100×19×26	15	4 960910 764163	10	
76417	for Rule and Square	71×19×25	17	4 960910 764170		
76418	T-shaped Model	80×55×15	21	4 960910 764187		
76423	Keyring Model	42×15×15	12	4 960910 764231		
76387	Clear Cube Model	75×30×15	38	4 960910 763876		
76347	Circular Model	45×11	10	4 960910 763470	6	
76065	Clip Model for Pole	66×35×94	35	4 960910 760653		
76064	Cube Model for Pole	43×61×34	35	4 960910 760646		

*Not available in certain areas. Please contact us for details.

Features

- Line clip model
 - With hook for leveling string
 - For measuring pipe by using V-shape groove
 - Can be used on flat surfaces as well
 - Portable with pocket clip
- For rule and square
 - Attachable on rule and square
 - Can be used on flat surfaces as well
 - Portable with pocket clip
- T-shape oval model
 - Measures four directions at the same time
 - Attach with screws to machine (Screws are not included)
- Key chain model
 - Easily check the horizontal level since 4 sides are measurement sides
 - Portable with large carabiner
- Clear Cube
 - All 6 sides have been processed as measuring surfaces
 - Place it flat to simultaneously measure two directions horizontally: front/back and left/right
- Circular model
 - Can be attached to machines and equipment with screws (M3 size: not included)
 - Can check the horizontal surface in all directions
- Clip type for poles
 - Clip and band can be freely attached to the measurement object
 - Large vial (φ25 mm) for high visibility
- Cube type for poles
 - Large vial (φ25 mm) for high visibility
 - Band (natural length: approx. 300 mm) provided conveniently attaches to the measurement object
 - V-shaped groove for pipe measurement

BLUE EYE



Use

- For verifying horizontality
- Mount on a pole or staff for vertical confirmation (76065)
- For vertical reference when installing pin poles (76065)
- Mount on a pole for horizontal or vertical confirmation (76064)

Specifications

Item Code	76416	76417	76418	76423	76387	76347
Sensitivity, Precision	Sensitivity 0.5 mm/m = 0.0286° Precision ±2.5 mm/m = less than ±0.1432°					
Material	Body: ABS resin Vial: Acrylic resin Liquid: Petroleum liquid			Body: Acrylic resin Liquid: Petroleum liquid Carabiner: Aluminum (76423)		

Item Code	76065		76064	
Supported pole diameter	Pole: 25 - 32 mm Pin poles: 4, 6 - 8 mm		—	
Sensitivity, Precision	Sensitivity 0.5 mm/m = 0.0286° Precision ±5.0 mm/m = less than ±0.2865°			
Use Temperature	-10 - 60°C			
Material	Body, Clip: polycarbonate resin Vial: Acrylic resin Liquid: Petroleum liquid		Body: ABS resin Vial: Acrylic resin Liquid: Petroleum liquid	
Accessories	Band (natural length approx. 300 mm)			

*When attached to a pole or staff (76065 only).

*When attached to a pole or staff (76065 only).