

Circular Saw Guide L-Angle Plus



73152



73150

73151

73153

● Parts are listed from p.274


Item Code	Description	Body Size (mm)	Weight (g)	JAN Code	Packing Unit	Packaging
73150	45 cm/shaku	632x350x83	1,100	4 960910 731509	2	
73151	60 cm/shaku	762x350x83	1,200	4 960910 731516		
73152	1 m/shaku	1,162x400x83	1,600	4 960910 731523	1	
73153	1.2 m/shaku	1,362x400x83	1,700	4 960910 731530		

Refer to p.2 about the shaku scale

New catalog items English package With red numbers Japanese zodiac signs cm/shaku (Upper side (or Front) metric / Lower side (or Back) shaku) shaku/cm (Upper side (or Front) shaku / Lower side (or Back) metric) With magnet
 With non-slip pad With battery Lithium-ion battery (Li-ION) Vial with luminous sheet With groove for slider Optional JCSS certificate Optional general calibration certificate

Features

● Slides in easily and secures tightly with Slide-Stop System. It slides smoothly since the non-slip rubber is normally floating above the surface. Pressing down on the handle causes the rubber portion to move down and adhere to the material, securing it tightly.



● Wide Hex Grip that grips securely.



● Heel shape that stands completely straight. The product will not become diagonal when stood upright since the guide and the handle mounting board have the same height.



● Enables square cuts just by aligning base plate of electric circular saw along the edge of the guide

● Features both shaku and metric graduations to come in handy for carpenters

● Aluminum construction makes guide both light and sturdy. Features white graduations on a blue background.

● With 303 mm and 455 mm guides

● Non-slip rubber pad achieves high non-slip performance thanks to the use of the high-performance microcellular polymer sheet PORON®, which has a high-density, delicate and uniform cell structure



● With groove for slider (sold separately, item code 78236) – just slide it in the groove to prevent shifting during cutting

● Stainless steel plate on guide edge

Use

- As a guide rule when making square cuts on boards with an electric circular saw
- For dimension measurements
- For cutter guides

Specifications

Item Code	73150	73151	73152	73153
Perpendicularity	Less than 0.5 mm per 500 mm	Less than 0.6 mm per 600 mm	Less than 1 mm per 1,000 mm	Less than 1.1 mm per 1,100 mm
Graduation	1 shaku 6 sun 5 bu	2 shaku	3 shaku 3 sun	4 shaku
Blade Size	50 cm	60 cm	1 m	1.2 m
Edge Height	632x82.5x7 mm	762x82.5x7 mm	1,162x82.5x7 mm	1,362x82.5x7 mm
Material	Body: Aluminum Guide Surface: Stainless steel Protective End Cap: ABS resin Wide Handle: ABS resin, elastomer resin			
Accessories	Cutout positioning stick			

Carpenter's Squares	Stainless Steel Rules/Machine Scale	Aluminum Rules	Squares/Protractors	Veneer Calipers/Micrometers
Surveying Products	Scales	Levels	Lasers/Optical Equipment	Inclinometers/Chalklines/Plumbholders
Construction Tools	Industrial Tools	Thermometers/Hygrometers/Environmental Measuring Instruments	Circular Saw Tools	Thermometers/Hygrometers/Environmental Measuring Instruments
Outdoor Products	Magnifying Glasses	Drawing Tools	Thermometers/Hygrometers/Environmental Measuring Instruments	Thermometers/Hygrometers/Environmental Measuring Instruments
Industrial Tools	Magnifying Glasses	Drawing Tools	Thermometers/Hygrometers/Environmental Measuring Instruments	Thermometers/Hygrometers/Environmental Measuring Instruments