

Circular Saw Guide Free Angle One-touch



Back
Securely lock guide onto material with one-touch lever



78450

●Parts are listed from p.274

Item Code	Description	Body Size (mm)	Weight (g)	JAN Code	Packing Unit	Packaging
78450	1 m	1,230×425×30	2,200	4 960910 784505	1	
78451	1.2 m	1,460×425×30	2,500	4 960910 784512	1	

Features

- One-touch operation for fixing and releasing
- An electric circular saw can be operated with both hands
- Easy-to-read gradient graduation
- Clear polycarbonate board helps to see cutting point
- Pin can be used to fix on soft material such as plasterboard

Use

- As a guide rule when making angular cuts on lumber with an electric circular saw

Specifications

Item Code	78450	78451
Perpendicularity (at 90°)	Less than 3.5 mm per 1,000 mm	
Edge Height	10 mm	
Material	Body: Stainless steel, aluminum Stopper Screw: Stainless steel, brass Assist plate: Polyacetal resin	
Accessories	Assist plate (Width: 123 mm Thickness: 2 mm)	

Circular Saw Guide Mini Free Angle Justy



78079



78176

●Parts are listed from p.274

Item Code	Description	Body Size (mm)	Weight (g)	JAN Code	Packing Unit	Packaging
78079	Quick Adjust 23 cm	350×105×26	360	4 960910 780798	4	
78176	II 23 cm	350×105×26	360	4 960910 781764	5	

Features

- Adjustable to any angle from 20 - 160°
- Gradient graduation from 3 sun to 8 sun
- Turn over to use on wider material
- Quick Adjust
 - Easily lock at certain angles (45°, 90°, 135°)
 - Flat stopper screw that does not interfere with an electric circular saw (78079/78217)
- Justy II/Mini Free Angle II
 - Easy-to-read black lettering on white graduation board
 - Uses sturdy metal screws that are not easily damaged instead of plastic screws that don't stand up well against impact
 - Flat folding screw

Use

- As a guide rule when making angular cuts on lumber with an electric circular saw
- As a guide rule when making cuts based on angles scribed from other materials

Specifications

Circular Saw Guide Mini Free Angle



78217



78179

●Parts are listed from p.274

Item Code	Description	Body Size (mm)	Weight (g)	JAN Code	Packing Unit	Packaging
78217	Quick Adjust 30 cm	439×100×26	460	4 960910 782174	4 (24)	
78179	II 30 cm	439×112×23	450	4 960910 781795	5	

■23 cm

Item Code	78079	78176
Perpendicularity (at 90°)	Less than 1 mm per 300 mm	
Edge Height	a: 9 mm	b: 8 mm
Material	Body: Stainless steel Stop Switch: ABS resin, polyacetal resin Stopper Screw: Stainless steel, brass Stopper Screw (flat): ABS resin	Body: Stainless steel Stopper Screw: Stainless steel, brass
Accessories	Cutout positioning stick Stopper screw (flat)	—

■30 cm

Item Code	78217	78179
Perpendicularity (at 90°)	Less than 1 mm per 300 mm	
Edge Height	a: 9 mm	b: 7 mm
Material	Body: Stainless steel, aluminum Stop Switch: ABS resin, polyacetal resin Stopper Screw: Stainless steel, brass Stopper Screw (flat): ABS resin	Body: Stainless steel, aluminum Stopper Screw: Stainless steel, brass
Accessories	Cutout positioning stick Stopper screw (flat)	—