Packaging  Ⓢ Shrink package  Ⓑ Box  Ⓥ Vinyl package + header card  Ⓥ Vinyl package  Ⓒ Clear package
Ⓢ Sleeve package  Ⓑ Bag  Ⓥ Bag + header card  Ⓒ Card  ⊘ No package

Thermometers/Hygrometers/
16. Environmental Measuring Instruments

SHINWA
2023

# Thermo/Hygrometer for Heatstroke Warning



**70505**

**70507**

**70515**

| Item Code | Description | | Body Size (mm) | Weight (g) | JAN Code | Packing Unit | Packaging |
|---|---|---|---|---|---|---|---|
| 70505 | F-3LⅡ 15 cm White | CAL | φ156×30 | 150 | 4 960910 705050 | | |
| 70507 | F-3M 10 cm White | CAL | φ106×30 | 73 | 4 960910 705074 | 5 | Ⓢ |
| 70515 | F-3S 6.5 cm White | CAL | φ71×21 | 33 | 4 960910 705159 | | |

## Features

- ●Shows five levels of warning for heatstroke



- ●With hook hole

## Use

- ●For temperature and humidity control at homes, in classrooms and offices, etc.
- ●As a guide for heat stroke prevention

### Specifications

| Item Code | 70505 | 70507 | 70515 |
|---|---|---|---|
| Accuracy | <Temperature> −20 - 40℃: ±2℃ | | |
| | <Humidity> 35 - 75%: ±5% Other values: ±10% | | |
| Measuring Range | Temperature: −20 - 40℃ | | |
| | Humidity: 30 - 80% | | |
| Each Graduation | Temperature: 2℃  Humidity: 5% | | |
| Material | Body: Polystyrene resin, ABS resin Scale Plate Cover: Polystyrene resin Scale Plate: Iron Pointer: Aluminum | | |

# Thermo/Hygrometer for Heatstroke Warning Rainproof

Rainproof structure offers protection even during rain.



**70600**

Large openings on back for quick response to changes in temperature, humidity, and heat stroke levels.

| Item Code | Description | | Body Size (mm) | Weight (g) | JAN Code | Packing Unit | Packaging |
|---|---|---|---|---|---|---|---|
| 70600 | F-3LⅡ 15 cm Red | CAL | φ156×38 | 160 | 4 960910 706002 | 5 | Ⓢ |

## Features

- ●Heatstroke warning indicator with rainproof function
- ●Shows five levels of warning for heatstroke
- ●With hook hole

## Use

- ●For temperature and humidity control in building, construction, farming, the home, classroom, or office, etc.
- ●As a guide for heat stroke prevention

### Specifications

| Accuracy | <Temperature>−20 - 40℃: ±2℃  Other values: ±4℃ |
|---|---|
| | <Humidity> 35 - 75%: ±5%  Other values: ±10% |
| Measuring Range | Temperature: −20 - 50℃ |
| | Humidity: 30 - 80% |
| Each Graduation | Temperature: 2℃ |
| | Humidity: 5% |
| Waterproof*1 | IPX3*2 |
| Material | Body: Polystyrene resin, ABS resin Scale Plate Cover: AS resin Scale Plate: Iron   Pointer: Aluminum Waterproof Cloth: Nylon, polyurethane resin |

*1 Waterproof performance protects internal functions, but device cannot measure accurately when wet.
*2 Not adversely affected by rain falling within 60° from either left or right.

NEW New catalog items  En English package  Red With red numbers  12 Japanese zodiac signs  cm/shaku (Upper side (or Front) metric/ Lower side (or Back) shaku)  shaku/cm (Upper side (or Front) shaku/ Lower side (or Back) metric)  With magnet
With non-slip pad  With battery  Lithium-ion battery (LI-ION)  Vial with luminous sheet  With groove for slider  CAL Optional JCSS certificate  CAL Optional general calibration certificate

220